

WERMA IO-Link Products

WERMA offers three signal tower solutions with the standardised IO-Link technology to enable sensor/actuator communication.

Monitor your processes, make them reliable and keep them running - saving time and money. We call this intelligent signalling technology.



Completely pre-assembled Signal Tower (4 tier)

ClearSIGN IO-Link

Dimensions (Ø x Height)	103,2 mm x 320 mm
Protection rating	IP 66
Sound output	85 dB
Connection	M12 (4 pin)
Cable entry	Cable diameter max. 11 mm
Voltage	24 V DC
Current consumption	385 mA (without buzzer) 425 mA (with buzzer)
Feature	<ul style="list-style-type: none">· Over 1 m colour variants possible· Different lighting modes· Fill level indicator· Individual parameterisation
IO Link without buzzer	656 100 02
IO Link with buzzer	656 100 03



ClassicLOOK

DesignLOOK

KombiSIGN 72

Terminal element	IO-Link	ClassicLOOK	DesignLOOK
Dimensions (Ø x Height)		70 mm x 65,5 mm	
Protection rating		IP 65	
Sound output		Max. 105 dB	
Cable entry		Cable diameter max. 11 mm	
Connection		CAGE CLAMP® technology max. 1,5mm ²	
Number of tiers possible		Max. 5	
Voltage		24 V via IO Link	
Current consumption		6 mA	
Feature		Switching on and off the signal elements	
IO Link Terminal element		646 840 55	646 440 55



ClassicLOOK

DesignLOOK

KombiSIGN 40

Terminal element	IO-Link	ClassicLOOK	DesignLOOK
Dimensions (Ø x Height)		40 mm x 58,6 mm	
Protection rating		IP 66	
Sound output		Max. 95 dB	
Cable entry		Cable diameter max. 9 mm	
Connection		Push-in terminal max. 0,75 mm ²	
Number of tiers possible		Max. 5	
Voltage		24 V via IO-Link	
Current consumption		10 mA	
Feature		Switching on and off the signal elements	
IO Link Terminal element		631 800 55	631 400 55

