



Floor Standing Server Cabinets


Simple design combined with high quality and functionality makes the cabinet very user-friendly. Latest technology employed in production results in the optimum parameters of stiffness, airiness (80%) or load capacity (1000 kg). Cabinets come with welded or modular versions. The wide type range of the cabinets and numerous accessories allow for any given configuration.




Perforated mesh with 80% airiness ensuring optimum air exchange in the cabinet



Door protected with 3 - point locking system ensuring equipment safety



Additional side cable entries in base and roof allow for perfect organization of cabling outside the 19" area (in 800 mm wide cabinets).



Frame and mounting sections structure with a load capacity of 1000 kg as a standard.

Floor Standing Server Cabinets

Available dimensions

| Type | Width (mm) | Depth (mm) | Height (mm) | Door front | Door rear | Index RAL7035 | Index RAL7021 | | |
|------|------------|------------|-------------|------------|-----------|------------------|------------------|------------------|------------------|
| 42U | 600 | 1000 | 1980 | 3 | 5 | SSRS4260103511.1 | SSRS4260103511.2 | | |
| | | 1000 | 1980 | 3 | 3 | SSRS4260103311.1 | SSRS4260103311.2 | | |
| | | 1200 | 1980 | 3 | 5 | SSRS4260123511.1 | SSRS4260123511.2 | | |
| | | 1200 | 1980 | 3 | 3 | SSRS4260123311.1 | SSRS4260123311.2 | | |
| | 800 | 1000 | 1980 | 3 | 5 | SSRS4280103511.1 | SSRS4280103511.2 | | |
| | | 1000 | 1980 | 3 | 3 | SSRS4280103311.1 | SSRS4280103311.2 | | |
| | | 1000 | 1980 | 4 | 4 | SSRS4280104411.1 | SSRS4280104411.2 | | |
| | | 1000 | 1980 | 3 | 4 | SSRS4280103411.1 | SSRS4280103411.2 | | |
| | | 1200 | 1980 | 3 | 5 | SSRS4260123511.1 | SSRS4280123511.2 | | |
| | | 1200 | 1980 | 3 | 3 | SSRS4260123311.1 | SSRS4280123311.2 | | |
| | | 45U | 600 | 1000 | 2120 | 3 | 5 | SSRS4560103511.1 | SSRS4560103511.2 |
| | | | | 1000 | 2120 | 3 | 3 | SSRS4560103311.1 | SSRS4560103311.2 |
| 1200 | 2120 | | | 3 | 5 | SSRS4560123511.1 | SSRS4560123511.2 | | |
| 1200 | 2120 | | | 3 | 3 | SSRS4560123311.1 | SSRS4560123311.2 | | |
| 800 | 1000 | | 2120 | 3 | 5 | SSRS4580103511.1 | SSRS4580103511.2 | | |
| | 1000 | | 2120 | 3 | 3 | SSRS4580103311.1 | SSRS4580103311.2 | | |
| | 1000 | | 2120 | 4 | 4 | SSRS4580104411.1 | SSRS4580104411.2 | | |
| | 1000 | | 2120 | 3 | 4 | SSRS4580103411.1 | SSRS4580103411.2 | | |
| 48U | 600 | 1200 | 2120 | 3 | 5 | SSRS4580123511.1 | SSRS4580123511.2 | | |
| | | 1200 | 2120 | 3 | 3 | SSRS4580123311.1 | SSRS4580123311.2 | | |
| | | 1000 | 2186 | 3 | 5 | SSRS4760103511.1 | SSRS4760103511.2 | | |
| | | 1000 | 2186 | 3 | 3 | SSRS4760103311.1 | SSRS4760103311.2 | | |
| | 800 | 1200 | 2186 | 3 | 5 | SSRS4760123511.1 | SSRS4760123511.2 | | |
| | | 1200 | 2186 | 3 | 3 | SSRS4760123311.1 | SSRS4760123311.2 | | |
| | | 1000 | 2186 | 3 | 5 | SSRS4780103511.1 | SSRS4780103511.2 | | |
| | | 1000 | 2186 | 3 | 3 | SSRS4780103311.1 | SSRS4780103311.2 | | |
| | | 1000 | 2186 | 3 | 5 | SSRS4780123511.1 | SSRS4780123511.2 | | |
| | | 1000 | 2186 | 3 | 3 | SSRS4780123311.1 | SSRS4780123311.2 | | |

Basic parameters

- Material: steel sheet
- Front door: one - piece perforated or two - piece perforated
- Rear door: one - piece perforated, two - piece perforated, perforated shortened wall
- Side walls: steel sheet
- Load capacity: 1000 kg
- IP rating: 20
- Colour: light grey RAL 7035 or black RAL 7021

Maximum spacing of mounting sections depending on cabinet depth:

- cabinets with a depth of 1000 mm - maximum spacing: 872 mm
- cabinets with a depth of 1200 mm - maximum spacing: 1072 mm

Regulatory compliance:

EIA-310-D, IEC 60297-1, IEC 60297-2, ROHS

Included in delivery:

- brush strip
- set of M6 assembly bolts (16 pcs)
- set of floor - leveller feet
- 1,5 m edge sealing
- 2 pairs of mounting sections

* other configurations available on request

