

Product information

Unassembled Standing Cabinets "Quick Rack"

An ideal solution for situations in which it is necessary to mount telecommunications cabinets in an environment not suitable for development (i.e. narrow server room doors, top floor building installations). Practically tool-free and simple cabinet mounting (mounting using 16 pcs M8 screws) reduces time and cost of installation. An important advantage of the "Quick Rack" solution is the reduction of transportation costs along with increased warehouse space.

- Surface finish: powder painted in RAL 7035 - light grey (other colors on request),
- Protection IP20 in accordance with PN 92/E-08106/EN 60529/IEC 529. (does not apply to brush cable entries),
- Indoor use,
- Cabinets can be arranged in line using line-up bolts after removing side walls (Part No.11190130),
- Cabinets are mounted according to the base and roof (2mm thick steel) with welded mounting holds for the corner profile (1.5mm thick steel). Each profile is mounted using four screws (2 to the base + 2 to the roof),
- Cabinet frame fully welded - 1,5 mm thick sheet steel on 4 x leveling feet M10,
- Optionally:
 - standard plinth
 - cabinet wheel kit - 11090015 (maximum load capacity 150 kg.)
- Front door: window made of safety glass 4 mm thick (optionally: full steel, full glass, punched perforated plate), opening angle 180 degrees,
- Left or right door opening options,
- Cabinet rear panel – 0.8 mm. thick sheet steel, removable with two single point locks (Optionally: full steel or perforated, left or right side mounted door),
- Cabinet side panels – 0.8 mm thick sheet steel, removable with two single point locks.



- Two pairs of profile rails (AL-Zn coated) each arranged at the front and rear on the inside. Each profile with unit labeling,
- Maximum spacing between front and rear profile rails:
 - cabinet depth 600 mm - max 472 mm
 - cabinet depth 780 mm - max 652 mm
- Possibility to increase maximum weight of equipment mounted in the cabinet SRS by using cabinet max load strengthening kit,
- Cables let in entry optionally either from roof or base, either, through top or bottom of the rear side of cabinet, pre-punched opening (Dimensions: 450 x 90 mm),
- In the roof and base of cabinet 2 x 4U blind plates (pre - punched opening) for fan units (possible configurations 1 or 2 x 2 fan units, 1 x 4 fan units, 1 x 6 fan units),
- Wide range of supplementary accessories: plinths, shelves, fan units, light units, power distribution units, blanking covers, cable management accessories etc,
- Optional 19" swing frame 90° opening.

Product information

Unassembled Standing Cabinets "Quick Rack"



Available dimensions

Type	Dimensions [mm]			Index
	Width	Depth	Height	
42U	600	600	1980	11058661.1V5
42U	600	780	1980	11025671.1V5
42U	780	780	1980	11058771.1V5